

**FAIR MATE**<sup>®</sup>  
**CHEMICALS PVT. LTD.**

Visit us at : [www.fairmate.net](http://www.fairmate.net) / [www.waterproofing4u.com](http://www.waterproofing4u.com)

Email : [sales@fairmate.net](mailto:sales@fairmate.net)

# FAIRFIX TA STD<sup>TM</sup>

## CERAMIC TILE ADHESIVE

### BENEFITS

- Prepacked factory controlled ensures consistent quality.
- Excellent adhesion - hence can be used tile on tile.
- Excellent waterproofing characteristics.
- Easy to use.
- Good slip resistance.

### PRODUCT

Prepacked Cementitious tile adhesive which ensures excellent bond on concrete, plastered and even on ceramic and mosaic tile surfaces. **FAIRFIX TA STD** ensures perfect watertightness.

### USES

**FAIRFIX TA STD** is a high quality adhesion for permanent fixing of ceramic tiles. Used for fixing of insulating & acoustic boards. Used in wet areas like kitchens & bathrooms.

### DESCRIPTION

**FAIRFIX TA STD** is a adhesive for the permanent fixing of ceramic tiles both in damp and submerged conditions. **FAIRFIX TA STD** can also be used for fixing tile on tile.

### STANDARD

Conforming to **BS 5980 Class AA Type 1** and suitability for contact with potable water as per **BS 6920, part 1**.

### APPLICATION

**Surface Preparation** : All surfaces must be sound and thoroughly cleaned before **FAIRFIX TA STD** is applied. All traces of greases or oil must be removed with **FM Degreaser**. All loose particles of mortar and points must be physically removed.

**Surfaces** : **FAIRFIX TA STD** can be applied directly on concrete, cement screeds, cement, lime mortars and existing tiles.

**Mixing** : **FAIRFIX TA STD** should be mixed with water in the ratio of 3:1 by volume. Water can be reduced or increased slightly to increase required consistency. A slow speed drill fitted with a suitable mixing paddle is recommended. Hand mixing may be allowed if drill/paddle is not available.

**Joints** : It is recommended that when fixing ceramic tiles, a minimum spacing of 2mm be left around each tile.

**Finishing** : Remove excess adhesive with a damp cloth before material has set. Joint grouting may be commenced 24 hours after tiles have been laid.

**Cleaning** : **FAIRFIX TA STD** should be removed from tools, equipment and mixers with clean water immediately after use cured material can only be removed mechanically.

### PACKING & COVERAGE

**FAIRFIX TA STD** is supplied in 25 kg HDPE bag.

25 kg of **FAIRFIX TA STD** will cover 5 to 8m<sup>2</sup> with recommended thickness of 3 to 4 mm.

### SHELF LIFE & STORAGE


**FAIRFIX TA STD** will have a shelf life of **24 months** in unopened containers when kept in dry conditions at a temperature between 5°C to 45°C. Storage at higher temperature or high humidity may reduce shelf life.

### HEALTH & SAFETY

**FAIRFIX TA STD** is non-toxic. However, splashes on the skin should be washed well with water and in contact with eye occurs, wash well with water and seek medical advise.

### SPECIFICATION

**FAIRFIX TA STD** is prepacked cementitious tile adhesive which ensures excellent bond on concrete, plastered and even on ceramic and mosaic tile surface with a packing of 25kg and will cover 5 to 8m<sup>2</sup> with recommended thickness 3 to 4mm in accordance with the instruction of FAIRMATE.



## QUALITY ASSURANCE

Fairmate manufactures entire range of construction chemicals under compliance of ISO 9001, ISO (EMS) 14001 & OHSAS 18001 (Occupational Health and Safety) certified by ISOQAR / UK.

## TECHNICAL SERVICES

While new advances and changes will take place but one thing will never change is quality and meeting special needs of our customers. Our laboratory in Baroda and technical personnel & experts are available to provide additional information and technical assistance. We are eager to work with you in development of new product and resolve your problem.

## OUR RANGE OF PRODUCTS

<b>CONCRETE ADMIXTURES</b> <b>WATERPROOFING SYSTEMS</b> <b>ENGINEERING GROUTS</b>	<b>INDUSTRIAL FLOOR SURFACES</b> <b>CONCRETE REPAIRS</b> <b>SURFACE TREATMENT</b>	<b>PREPACKED CONCRETE MORTAR</b> <b>PROTECTIVE COATING</b> <b>HIGHWAY REPAIR</b>
---	---	--

"Contact us to discuss any potential requirement and you will be assured of a rapid and effective response - that's guarantee !!"



**BARODA** : 8/1, "SAI SUDHA", ARUNODAY SOCIETY, ALKAPURI, VADODARA-7 Tel. : (0265) 2358173-74, 2331193, 2331399 Fax : (0265) 2338733 Email : sales@fairmate.net  
**AHMEDABAD** : 1514, Ranchhod Bhuvan, Moti Vasan Sheri, Saraspur, Ahmedabad-18. Tel. : (079) 22923131, 26465219 Tel./Fax : 22923434 **BANGALORE** : Tel. 23639852 Tel./Fax : (080) 23639851 Email : bangalore@fairmate.net **DELHI** : Tel./Fax : (011) 27306224, 27306282 Mobile 9810032422 Email : delhi@fairmate.net **KOLKATA** : Tel. : (033) 24404932  
**MUMBAI** : Tel. : (022) 28794045, 28794044 Mobile 9820291610 Email : mumbai@fairmate.net **UDAIPUR** : Mobile 09829699943 **JAIPUR** : Mobile 09829688843 **LUCKNOW** : Mobile 9415022470 **SANGLI** : Mobile 09850817020 **PANIPAT** : Mobile 09813972551 **COCHIN** : Mobile 09847169473 **AGRA** : Mobile 09719402888 **JALANDHAR** : Mobile 09815039539 **DUBAI** : Tel. : +9716 5261052 Tel./Fax : +9716 5261053, +971 50 4355048 **NEPAL** : Tel. : +9771 5552723, Tel./Fax : +9771 5559949

The information given in this data sheet is based on both current development work and many years field experience. Whilst every effort is made to ensure that the information is reliable, we can not accept responsibility for any work carried out with our materials as we have no control over methods of application, site conditions etc. In view of the continuing research and development being undertaken in our laboratories we advise customers in their own interest to ensure that this data sheet has not been supersede by a more up-to-date publication. All products are sold subject to our standard conditions of sale which are available on request. Field services, where provided, does not constitute supervisory responsibility. For additional information, please contact your local FAIRMATE representative.